

cnPilot e410 Indoor

802.11ac wave 2 dual band 2x2 Indoor access point

The compact low profile 802.11ac Wave 2 Multi-user MIMO (MU-MIMO) beamforming, high speed e410 Enterprise access point, future-proofs your indoor access point deployments and is perfect for Schools, Indoor Public Spaces, Shopping Centres, Hotels and Resorts (Hospitality), Coffee Shops, Multi-dwelling units (MDUs) or just about any place indoor that needs reliable high performing access points.

CONTROLLER MANAGED & AUTONOMOUS

Managed by Cambium's cnMaestro™ cloud controller or on-premises controller, the cnPilot e410 management includes: • Zero touch onboarding • Inventory tracking • Monitoring • Mass configuration • Dashboard views with Alarms • Mass upgrade • Troubleshooting • Hierarchical device organisation

CONTROLLER-LESS ROAMING. POWERFUL SIMPLICITY

The e410 supports seamless roaming for up to 1,000 clients without needing a controller in the network. Hotspot portal hosting on the AP itself offers controller-less simplicity.

MONETISE YOUR NETWORK

cnMaestro's Guest access feature supports splash page hosting, social login and payment gateway. These features, the ability to create time, rate and volume limited traffic profiles along with vouchers for



temporary guest access makes the e410 ideal for Hotels, Coffee shops, Campgrounds, and Office guest WiFi.

SERVICE AWARE WLANS. BETTER USER EXPERIENCE

Nothing is more frustrating than connecting to an access point, but not getting to the Internet. When connection to a critical resource such as an external Gateway or AAA is down, the e410 can turn off the impacted SSIDs enabling client devices to select a different working neighboring access point.

INDOOR/OUTDOOR WI-FI MESH. FLEXIBILITY

Indoor meshing across multiple E410s or Indoor/Outdoor meshing across the indoor e410 and the outdoor e500. Offers a convenient way to easily expand WiFi coverage without wires.

COVERAGE, CAPACITY. SPEED

The plenum rated e410, packs a max transmit power of 25 dBm, and is DFS certified to make use of additional reserved 5GHz DFS channels, offering more flexibility for both coverage and capacity. Throughput management via Airtime fairness, increased performance by Automatic channel scanning (ACS), and higher client device speeds from Band steering ensure your network can adapt to the dynamics of ever changing client behaviours.

HIGH DENSITY, HIGHLY AVAILABLE

A capacity of 256 max concurrent client associations, and 16 SSIDs, along with dual on-board Active/Standby memory banks ensure the e410 combines high density with high availability.

LICENSE FREE HIGH PERFORMANCE. ONE LOW PRICE.

The 802.11ac wave 2 e410 comes with a free controller, and no AP management license fees. No hidden charges. Affordable.

ACCESS POINT OVERVIEW

Standards	IEEE 802.11a/b/g/n/ac Wave 2 Other Standards: 802.11 h/d/r/u/w
MIMO Streams	2x2 MU-MIMO Streams
Range	180 m (650 Ft)
Max Concurrent Clients	256
Max Data Rates	1.3 Gbs, 1,267Mbps
SSID	16 SSIDs across 2 radios
Antenna Gain	4.5 dBi (2.4GHz), 4.25 dBi (5GHz)
Multi-Hop Mesh	Yes. Supported on all cnPilot Indoor & Outdoor access points. Mesh auto-recovery supported.
Polarisation	Dual-Linear
Antenna Coverage	Omni (360°)
Ethernet Ports	One (1) x 1 Gigabit Ethernet (10/100/1000 Mbps)
Frequency Bands	2.4GHz: 2400-2484 MHz 5GHz: 5150-5850 MHz with DFS band support
Power Supply	Standard 802.3af injector (supplied) or any PoE switch
Power Consumed	13W (max)
Dimensions	170 x 170 x 41mm (17x17x4.1cm)
Weight	384 grams (0.384kg)
Temperature	0°C to + 50°C
LED	Single LED window with tri-colour LED (Amber, Blue, Green)
Max TX Power	+25 dBm
Physical Lock	Kensington Lock Slot