

# Wi-Fi 5

## Dual Band | 2x2:2 Outdoor Access Point



ion4



ion4\_2

### Carrier Grade

#### Managed Wi-Fi Solutions

- Captive Portal + AAA
- Voucher Management
- Web Self-care
- Policy Control
- Wi-Fi Network & Performance Analytics
- Configurable User Journey/Survey
- Footfall Analytics

### Cloud Management


#### Ease Of Management

- Centralized control
- Troubleshoot on the move
- Network analytics

#### Scalable Platform


- Create & Expand
- Robust & scalable application

# Ubiquitous Secure Connectivity



## Mesh Coverage

The entire Wi-Fi network functions on 802.11s Mesh technology. One or more Access Point can act as the controller (or Mesh root). With no limitation on the number of Agent nodes (or Mesh satellites) connected with each other or the Mesh root, the mesh network becomes highly scalable. Mesh limits the need for ethernet cabling to one or just a few cables. It is designed to eliminate wireless dropouts, stuttering videos, slow download speeds, poor signal and Wi-Fi dead zones.




## Self-healing Mesh

In case of a mesh node failure, the surrounding nodes automatically re-connect and resume service without downtime. Nodes identify the best next hop and connect with it automatically.



## Band Steering

In highly congested environments, the Access Point automatically moves dual-band client devices onto the wider 5GHz band for faster connections.



## MIMO

Multiple Input and Multiple Output: This multiplies capacity by simultaneously transmitting & receiving from multiple devices.



## Ease of Installation

Access Points can be mounted on walls & poles. Freedom of movement of Access Points even after installation in both horizontal and vertical axis for quick and easy alignment.

# Outdoor Access Point

Our Wi-Fi 5 outdoor access points come packed with a plethora of features. They come with high performance antennas that ensure that there are no dead zones, while their IP67 rated bodies are ready for all weather conditions and are built to last.



## WIRELESS

|                       |  |
|-----------------------|--|
| Wi-Fi Standards       | 802.11a/b/g/n/ac/ac Wave 2   |
| Radio Mode            | 2x2 MU-MIMO with 2 spatial streams   |
| Radio Frequency Band  | Supports full 2.4 GHz & 5 GHz ISM frequency bands                                  |
| Peak Throughput       | Upto 1.27 Gbps (867 Mbps for 5 GHz and 400 Mbps for 2.4 GHz)                       |
| Max Transmit Power    | 27 dBm for 2.4 GHz , 27 dBm for 5 GHz (will depend on country-specific guidelines) |
| Receiver Sensitivity  | -97 dBm (for MCS 0)  |
| Channel Size          | 20/40/80 MHz   |
| Modulation Schemes    | Supports upto 256 QAM  |
| User Support          | 128 on 5 GHz and 64 on 2.4 GHz   |
| Power                 | IEEE 802.3af PoE   |
| Max Power Consumption | 12 W (approx..)  |
| Interface             | 1x10/100/1000BASE-T Ethernet   |
| Antenna               | Integrated directional antennas with 90° beamwidth                                 |
| Antenna gain          | 8 dBi for 2.4 GHz and 5 GHz (ion4)<br>14 dBi for 2.4 GHz and 5 GHz (ion4_2)        |

## SECURITY & FEATURES

### Security

WPA-Personal, WPA2-Personal, WPA2-Enterprise, EAP Type (EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0/EAP-MSCHAPv2, PEAPv1/EAP-GTC, EAP-SIM, EAP-AKA, EAP-AKA Prime, EAP-FAST), Protected Management Frames, VPN pass-through, IP Security (IPSec), PPTP, IP-Filtering, Layer 2 Tunneling Protocol (L2TP/LWAP/AMQPS/GRE), Flexible guest access with device isolation, Captive portal and guest accounts, Rogue access point detection and prevention, Hidden SSID in beacons, MAC address authentication, X.509 digital certificates, Support for locally-significant certificates using Public Key Infrastructure (PKI)

### High Level Features

WAN Protocols: Static IPv4/v6, DHCP client v4/v6, Band Steering, Load Balancing, Channel Bonding, WDS and MESH Support, Auto Channel Selection, Intelligent RF control plane for self-healing and self-optimization, Ability to simultaneously serve clients and monitor RF environment, Radio Resource Management for power and channel, Management: Standalone (via GUI) or through appliance-based WLC and EMS or cloud-based, 16 SSID per Radio, QOS 802.11e WMM, 802.11r- fast roaming and fast handover, Bandwidth Shaping per SSID, Maximal ratio combining (MRC) and beamforming support, 802.11w- Protected Management Frames (PMF) support, Advance Power Save (U-APSD), VoIP support

## PHYSICAL & ENVIRONMENTAL

|  |  |
|--|--|
| <b>Enclosure</b>                         | Two-piece enclosure with UV protected ABS + PC top and bottom body, and an aluminium heat sink at bottom |
| <b>Dimensions</b>                        | 185 X 170 X 65 mm ( 7.28 x 6.69 x 2.56 in) (ion4)<br>370X215X86 mm (14.56X8.46X3.38 in) (ion4_2)         |
| <b>Weight</b>                            | 0.75 kg (ion4)<br>1.5 kg (ion4_2)  |
| <b>Mounting</b>                          | Pole and wall mounting<br>Turning Angle: 140° H & 60° V<br>Weight: 185 grams                             |
| <b>Visual Indicators</b>                 | RF and Power LEDs  |
| <b>Operating Temperature</b>             | -15° C to 60° C  |
| <b>Operating Humidity</b>                | 5 to 95% (non-condensing)  |
| <b>Wind Sustainability</b>               | 150 km/hour (sustained winds)  |
| <b>Certifications</b>                    | FCC Class A, CE,<br>Wi-Fi Certified Passpoint 2.0  |
| <b>Outdoor Ingress Protection Rating</b> | IP67   |

## SAFETY & OTHER COMPLIANCES


### Safety

- Safety Protection as per IEC 60950 and IEC 60215
- Electrostatic Discharge Immunity as per IEC 61000-4-2, Contact L2 and Air Discharge, L3 Level
- DC Surge Immunity as per IEC 61000-4-5, Level 2 (power port + signal port)
- Electrical Fast Transient/Burst Immunity as per IEC 61000-4-4, Level 2
- Radiated susceptibility as per IEC 61000-4-3 Level 2
- Conducted Susceptibility as per IEC 61000-4-6, Level 2
- Bump and vibration as per QM333

### Other Compliances

- Radiated Emission as per CISPR 22 Class A
- Conducted Emission as per CISPR 22 Class A (power port + signal port)
- Voltage Variation: AC- as per IEC 61000-4-11 and DC- as per IEC 61000-4-29

## TARGET APPLICATIONS



## ORDERING INFORMATION

| MODEL NUMBER | PRODUCT DESCRIPTION   |
|--------------|---|
| ion4         | IO Wi-Fi 5 Dual Band 2x2:2 Outdoor Access Point with Integrated Antenna (8 dBi) |
| ion4_2       | IO Wi-Fi 5 Dual Band 2x2:2 Outdoor Access Point with Integrated Antenna (14dBi) |



**Email:** [iosupport@hfcl.com](mailto:iosupport@hfcl.com)  
**Website:** [hfcl.com](http://hfcl.com) | [io.hfcl.com](http://io.hfcl.com)  
**Office:** 8, Commercial Complex, Masjid  
 Moth Greater Kailash II, New Delhi 110048